

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Lithium aluminium hydride, 1M solution in THF
Cat No. : 199490000; 199491000; 199498000
Synonyms LAH; Lithium tetrahydridoaluminate; Lithiumalanate
Molecular Formula Al H4 Li

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Sector of use SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites
Product category PC21 - Laboratory chemicals
Process categories PROC15 - Use as a laboratory reagent
Environmental release category ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

UK entity/business name
 Fisher Scientific UK
 Bishop Meadow Road,
 Loughborough, Leicestershire LE11 5RG, United Kingdom

EU entity/business name
 Thermo Fisher Scientific
 Janssen Pharmaceuticaaan 3a, 2440 Geel, Belgium

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

Flammable liquids	Category 2 (H225)
Substances/mixtures which, in contact with water, emit flammable gases	Category 1 (H260)

SAFETY DATA SHEET

Lithium aluminium hydride, 1M solution in THF

Revision Date 06-Dec-2024

Health hazards

Acute oral toxicity
Skin Corrosion/Irritation
Serious Eye Damage/Eye Irritation
Carcinogenicity
Specific target organ toxicity - (single exposure)

Category 4 (H302)
Category 2 (H315)
Category 1 (H318)
Category 2 (H351)
Category 3 (H335) (H336)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor
H260 - In contact with water releases flammable gases which may ignite spontaneously
H302 - Harmful if swallowed
H315 - Causes skin irritation
H318 - Causes serious eye damage
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer
EUH019 - May form explosive peroxides

Precautionary Statements

P280 - Wear protective gloves/protective clothing/eye protection/face protection
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor/physician
P231 + P232 - Handle and store contents under inert gas. Protect from moisture
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

2.3. Other hazards

Reacts violently with water
Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

Toxic to terrestrial vertebrates
This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

SAFETY DATA SHEET

Lithium aluminium hydride, 1M solution in THF

Revision Date 06-Dec-2024

3.2. Mixtures

Component	CAS No	EC No	Weight %	GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Tetrahydrofuran	109-99-9	203-726-8	96	Flam. Liq. 2 (H225) Acute Tox. 4 (H302) Eye Irrit. 2 (H319) STOT SE 3 (H335) STOT SE 3 (H336) Carc. 2 (H351) (EUH019)
Lithium aluminum hydride	16853-85-3	EEC No. 240-877-9	4	Skin Corr. 1A (H314) Eye Dam. 1 (H318) Water-react. 1 (H260)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Tetrahydrofuran	Acute Tox. 4 :: C>82.5% Eye Irrit. 2 :: C>=25% STOT SE 3 :: C>=25%	-	-

Components	Reach Registration Number
Tetrahydrofuran	01-2119444314-46
Lithium aluminum hydride	01-2119919039-36

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes severe eye damage. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Causes central nervous system depression

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically. Symptoms may be delayed.
---------------------------	---

SAFETY DATA SHEET

Lithium aluminium hydride, 1M solution in THF

Revision Date 06-Dec-2024

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Water. Carbon dioxide (CO₂). Foam.

5.2. Special hazards arising from the substance or mixture

Flammable. Contact with water liberates toxic gas. Water reactive. Produce flammable gases on contact with water. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Hydrogen.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Ensure adequate ventilation. Avoid ingestion and inhalation. If peroxide formation is suspected, do not open or move container. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

SAFETY DATA SHEET

Lithium aluminium hydride, 1M solution in THF

Revision Date 06-Dec-2024

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and flame. Protect from direct sunlight. Keep from any possible contact with water. Flammables area. Keep under nitrogen. Shelf life 12 months. May form explosive peroxides on prolonged storage. Keep container tightly closed in a dry and well-ventilated place. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 4.3

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Tetrahydrofuran	STEL: 100 ppm 15 min STEL: 300 mg/m ³ 15 min TWA: 50 ppm 8 hr TWA: 150 mg/m ³ 8 hr Skin	TWA: 50 ppm (8h) TWA: 150 mg/m ³ (8h) STEL: 100 ppm (15min) STEL: 300 mg/m ³ (15min) Skin	TWA: 50 ppm 8 hr. TWA: 150 mg/m ³ 8 hr. STEL: 100 ppm 15 min STEL: 300 mg/m ³ 15 min Skin

Biological limit values

List source(s):

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Tetrahydrofuran 109-99-9 (96)				DNEL = 12.6mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Tetrahydrofuran 109-99-9 (96)	DNEL = 300mg/m ³	DNEL = 96mg/m ³	DNEL = 150mg/m ³	DNEL = 72.4mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Tetrahydrofuran	PNEC = 4.32mg/L	PNEC = 23.3mg/kg	PNEC = 21.6mg/L	PNEC = 4.6mg/L	PNEC = 2.13mg/kg

SAFETY DATA SHEET

Lithium aluminium hydride, 1M solution in THF

Revision Date 06-Dec-2024

109-99-9 (96)		sediment dw			soil dw
-----------------	--	-------------	--	--	---------

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Tetrahydrofuran 109-99-9 (96)	PNEC = 0.432mg/L	PNEC = 2.33mg/kg sediment dw		PNEC = 67mg/kg food	

8.2. Exposure controls

Engineering Measures

Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Butyl rubber	See manufacturers recommendations	-	EN 374	(minimum requirement)
Neoprene gloves				

Skin and body protection

Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

SAFETY DATA SHEET

Lithium aluminium hydride, 1M solution in THF

Revision Date 06-Dec-2024

Physical State	Liquid	
Appearance	Grey	
Odor	Irritating	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	-17 °C / 1.4 °F	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	7	
Viscosity	No data available	
Water Solubility	Reacts violently with water	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Tetrahydrofuran	0.45	
Vapor Pressure	No data available	
Density / Specific Gravity	0.900	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Molecular Formula	Al H4 Li
Molecular Weight	37.95
Explosive Properties	Vapors may form explosive mixtures with air
Substances/mixtures which, in contact with water, emit flammable gases	Emitted gas ignites spontaneously Gas(es) = Hydrogen

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

; Yes Contact with water liberates extremely flammable gases

10.2. Chemical stability

Decomposes in contact with water. Moisture sensitive. heat sensitive. May form explosive peroxides.

10.3. Possibility of hazardous reactions

Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition. Excess heat. Exposure to light. Incompatible products. Exposure to moist air or water.

10.5. Incompatible materials

Acids. Water. Alcohols. Carbon dioxide (CO2). Oxidizing agent.

SAFETY DATA SHEET

Lithium aluminium hydride, 1M solution in THF

Revision Date 06-Dec-2024

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrogen.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Category 4

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Tetrahydrofuran	1650 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	180 mg/L (Rat) 1 h 53.9 mg/L (Rat) 4 h

(b) skin corrosion/irritation;

Category 2

(c) serious eye damage/irritation;

Category 1

(d) respiratory or skin sensitization;

Respiratory

Based on available data, the classification criteria are not met

Skin

Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
Tetrahydrofuran 109-99-9 (96)	Local Lymph Node Assay OECD Test Guideline 429	mouse	non-sensitising

(e) germ cell mutagenicity;

Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
Tetrahydrofuran 109-99-9 (96)	OECD Test Guideline 476 Gene cell mutation	in vivo Mammalian	negative
	OECD Test Guideline 473 Chromosomal aberration assay	in vitro Mammalian	negative

(f) carcinogenicity;

Category 2

The table below indicates whether each agency has listed any ingredient as a carcinogen
Limited evidence of a carcinogenic effect

Component	EU	UK	Germany	IARC
Tetrahydrofuran				Group 2B

(g) reproductive toxicity;

Based on available data, the classification criteria are not met

Component	Test method	Test species / Duration	Study result
Tetrahydrofuran 109-99-9 (96)	OECD Test Guideline 416	Rat 2 Generation	NOAEL = 3,000 ppm

(h) STOT-single exposure;

Category 3

SAFETY DATA SHEET

Lithium aluminium hydride, 1M solution in THF

Revision Date 06-Dec-2024

Results / Target organs Respiratory system, Central nervous system (CNS).

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Causes central nervous system depression.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects Reacts with water so no ecotoxicity data for the substance is available.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Tetrahydrofuran	2160 mg/l LC50 = 96 h Pimephales promelas Leuciscus idus: LC50: 2820 mg/L/48h	EC50 48 h 3485 mg/l EC50: >10000 mg/L/24h	

12.2. Persistence and degradability

Persistence Persistence is unlikely, based on information available.
Degradability Reacts with water.
Degradation in sewage treatment plant Reacts violently with water.

12.3. Bioaccumulative potential Bioaccumulation is unlikely; Product does not bioaccumulate due to reaction with water

Component	log Pow	Bioconcentration factor (BCF)
Tetrahydrofuran	0.45	No data available

12.4. Mobility in soil

The product is water soluble, and may spread in water systems Reacts violently with water . Will likely be mobile in the environment due to its water solubility. Is not likely mobile in the environment. Highly mobile in soils

12.5. Results of PBT and vPvB assessment

Reacts violently with water. Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

Component	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances
Tetrahydrofuran	Group III Chemical	

SAFETY DATA SHEET

Lithium aluminium hydride, 1M solution in THF

Revision Date 06-Dec-2024

12.7. Other adverse effects

Persistent Organic Pollutant
Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number

UN1411

14.2. UN proper shipping name

LITHIUM ALUMINIUM HYDRIDE, ETHEREAL

14.3. Transport hazard class(es)

4.3

Subsidiary Hazard Class

3

14.4. Packing group

I

ADR

14.1. UN number

UN1411

14.2. UN proper shipping name

LITHIUM ALUMINIUM HYDRIDE, ETHEREAL

14.3. Transport hazard class(es)

4.3

Subsidiary Hazard Class

3

14.4. Packing group

I

IATA

14.1. UN number

UN1411

14.2. UN proper shipping name

LITHIUM ALUMINIUM HYDRIDE, ETHEREAL

14.3. Transport hazard class(es)

4.3

Subsidiary Hazard Class

3

14.4. Packing group

I

14.5. Environmental hazards

No hazards identified

14.6. Special precautions for user

No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

SAFETY DATA SHEET

Lithium aluminium hydride, 1M solution in THF

Revision Date 06-Dec-2024

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Tetrahydrofuran	109-99-9	203-726-8	-	-	X	X	KE-33454	X	X
Lithium aluminum hydride	16853-85-3	240-877-9	-	-	X	X	KE-00990	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Tetrahydrofuran	109-99-9	X	ACTIVE	X	-	X	X	X
Lithium aluminum hydride	16853-85-3	X	ACTIVE	-	X	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Tetrahydrofuran	109-99-9	-	Use restricted. See entry 75. (see link for restriction details)	-
Lithium aluminum hydride	16853-85-3	-	Use restricted. See entry 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Tetrahydrofuran	109-99-9	Not applicable	Not applicable
Lithium aluminum hydride	16853-85-3	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

SAFETY DATA SHEET

Lithium aluminium hydride, 1M solution in THF

Revision Date 06-Dec-2024

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification Water endangering class = 1 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Tetrahydrofuran	WGK1	
Lithium aluminum hydride	WGK1	

Component	France - INRS (Tables of occupational diseases)
Tetrahydrofuran	Tableaux des maladies professionnelles (TMP) - RG 84

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Tetrahydrofuran 109-99-9 (96)		Group I	

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H260 - In contact with water releases flammable gases which may ignite spontaneously
H302 - Harmful if swallowed
H315 - Causes skin irritation
H318 - Causes serious eye damage
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer
EUH019 - May form explosive peroxides
H225 - Highly flammable liquid and vapor
H314 - Causes severe skin burns and eye damage
H319 - Causes serious eye irritation

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

SAFETY DATA SHEET

Lithium aluminium hydride, 1M solution in THF

Revision Date 06-Dec-2024

NOEC - No Observed Effect Concentration
PBT - Persistent, Bioaccumulative, Toxic

POW - Partition coefficient Octanol:Water
vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

Creation Date 24-Nov-2010
Revision Date 06-Dec-2024
Revision Summary Not applicable.

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet