

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 05-Jan-2011 Revision Date 17-Jul-2025 Revision Number 13

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THECOMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Aqualine™ Electrolyte A (Anolyte for general use)

Cat No. : K/2500/08

Synonyms Karl Fischer reagent

Unique Formula Identifier (UFI) EUEH-X215-3X07-SD38

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

UK entity/business name

Fisher Scientific UK

Bishop Meadow Road, Loughborough, Leicestershire LE11 5RG, United Kingdom

EU entity/business name Thermo Fisher Scientific Janssen Pharmaceuticalaan 3a

2440 Geel, Belgium

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

Tel: 01509 231166

Chemtrec US: (800) 424-9300 Chemtrec EU: 001-703-527-3887

Poison Centre - Emergency

information services

Ireland: National Poisons Information Centre (NPIC) -

01 809 2166 (8am-10pm, 7 days a week)

Malta: +356 2395 2000 Cyprus: +357 2240 5611

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

Flammable liquids Category 2 (H225)

Health hazards

Acute oral toxicity Category 3 (H301) Acute dermal toxicity Category 3 (H311) Acute Inhalation Toxicity - Vapors Category 3 (H331) Skin Corrosion/Irritation Category 1 B (H314) Serious Eye Damage/Eye Irritation Category 1 (H318) Carcinogenicity Category 2 (H351) Reproductive Toxicity Category 2 (H361d) Specific target organ toxicity - (single exposure) Category 1 (H370)

Specific target organ toxicity - (repeated exposure) Category 1 (H372)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled

H314 - Causes severe skin burns and eye damage

H351 - Suspected of causing cancer

H361d - Suspected of damaging the unborn child

H370 - Causes damage to organs

H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

P308 + P313 - IF exposed or concerned: Get medical advice/attention

Additional EU labelling

For use in industrial installations only

2.3. Other hazards

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Methyl alcohol	67-56-1	200-659-6	25-50	Flam. Liq. 2 (H225) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370)
Chloroform	67-66-3	200-663-8	10-20	Acute Tox. 4 (H302) Acute Tox. 3 (H331) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H336) Carc. 2 (H351) Repr. 2 (H361d) STOT RE 1 (H372)
2-Amino-2-methyl-1-propanol	124-68-5	EEC No. 204-709-8	10-20	Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Aquatic Chronic 3 (H412)
2,4,6-Collidine	108-75-8	EEC No. 203-613-3	10-20	Flam Liq. 3 (H226) Acute Tox. 4 (H302) Acute Tox. 3 (H311) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335)
Sulfur dioxide	7446-09-5	EEC No. 231-195-2	5-10	Press. Gas (H280) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Acute Tox. 3 (H331) STOT SE 1 (H370)
lodine	7553-56-2	231-442-4	5-10	Acute Tox. 4 (H302) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335) STOT RE 1 (H372) Aquatic Acute 1 (H400)
Toluene-4-sulfonic acid monohydrate	6192-52-5		0.1-1	Skin Corr. 1C (H314) Eye Dam. 1 (H318)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Methyl alcohol	STOT Single Exp. 1 :: >= 10 STOT Single Exp. 2 :: 3 - < 10	-	-
Chloroform	STOT RE 2 : C ≥ 5 %	-	-
Iodine	-	1	-

Components	Reach Registration Number	
Methanol	01-2119433307-44	
Chloroform	01-2119486657-20	
2-Amino-2-methyl-1-propanol	01-2119475788-16	
Sulfur dioxide	01-2119485028-34	
Iodine	01-2119485285-30	

Aqualine™ Electrolyte A (Anolyte for general use)

Full tout of Hammel Clatemanton and position 40

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In

the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Inhalation If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim

ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh

air. Immediate medical attention is required.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water mist may be used to cool closed containers. CO₂, dry chemical, dry sand, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Nitrogen oxides (NOx), Chlorine, Hydrogen halides, Formaldehyde.

5.3. Advice for firefighters

Revision Date 17-Jul-2025

Aqualine™ Electrolyte A (Anolyte for general use)

Revision Date 17-Jul-2025

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area. Corrosives area.

Technical Rules for Hazardous Substances (TRGS) 510 Class 3 Storage Class (LGK) (Germany)

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

Aqualine™ Electrolyte A (Anolyte for general use)

Revision Date 17-Jul-2025

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Methyl alcohol	WEL - TWA: 200 ppm TWA;	TWA: 200 ppm 8 hr	TWA: 200 ppm 8 hr.
	266 mg/m³ TWA	TWA: 260 mg/m ³ 8 hr	TWA: 260 mg/m ³ 8 hr.
	WEL - STEL: 250 ppm	Skin	STEL: 600 ppm 15 min
	STEL; 333 mg/m ³ STEL		STEL: 780 mg/m ³ 15 min
			Skin
Chloroform	TWA: 2 ppm	TWA: 2 ppm 8 hr	TWA: 2 ppm 8 hr.
	TWA: 9.9 mg/m ³	TWA: 10 mg/m ³ 8 hr	TWA: 9.8 mg/m ³ 8 hr.
	STEL: 6 ppm	Possibility of significant	STEL: 6 ppm 15 min
	STEL: 29.7 mg/m ³	uptake through the skin	STEL: 29.4 mg/m ³ 15 min
			Skin
Sulfur dioxide	STEL: 1 ppm 15 min	TWA: 1.3 mg/m ³ (8h)	TWA: 0.5 ppm 8 hr.
	STEL: 2.7 mg/m ³ 15 min	TWA: 0.5 ppm (8h)	TWA: 1.3 mg/m ³ 8 hr.
	TWA: 0.5 ppm 8 hr	STEL: 2.7 mg/m ³ (15min)	STEL: 2.7 mg/m ³ 15 min
	TWA: 1.3 mg/m ³ 8 hr	STEL: 1 ppm (15min)	STEL: 1 ppm 15 min
lodine	STEL: 0.1 ppm 15 min		TWA: 0.01 ppm 8 hr.
	STEL: 1.1 mg/m ³ 15 min		inhalable fraction and vapour
			TWA: 0.01 mg/m ³ 8 hr.
			STEL: 0.1 ppm 15 min

Biological limit values

List source(s):

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Methyl alcohol		DNEL = 20mg/kg		DNEL = 20mg/kg
67-56-1 (25-50)		bw/day		bw/day
Chloroform 67-66-3 (10-20)				DNEL = 0.94mg/kg bw/dav
2-Amino-2-methyl-1-propanol 124-68-5 (10-20)				DNEL = 7.3mg/kg bw/day
lodine 7553-56-2 (5-10)				DNEL = 0.01mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Methyl alcohol 67-56-1 (25-50)	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³
Chloroform 67-66-3 (10-20)		DNEL = 333mg/m ³	DNEL = 2.5mg/m ³	DNEL = 2.5mg/m ³
2-Amino-2-methyl-1-propanol 124-68-5 (10-20)				DNEL = 6.5mg/m ³
Sulfur dioxide 7446-09-5 (5-10)	DNEL = 2.7mg/m ³		DNEL = 2.7mg/m ³	
lodine 7553-56-2 (5-10)				DNEL = 0.07mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component Fresh water Fresh water Water Intermittent Microorganisms in Soil (Agriculture)

Aqualine™ Electrolyte A (Anolyte for general use)

Revision Date 17-Jul-2025

		sediment		sewage treatment	
Methyl alcohol	PNEC = 20.8mg/L	PNEC = 77mg/kg	PNEC = 1540mg/L	PNEC = 100mg/L	PNEC = 100mg/kg
67-56-1 (25-50)		sediment dw			soil dw
Chloroform	PNEC = 0.146mg/L	PNEC = 0.45 mg/kg	PNEC = 0.133mg/L	PNEC = 0.048mg/L	PNEC = 0.56mg/kg
67-66-3 (10-20)	-	sediment dw		-	soil dw
2-Amino-2-methyl-1-propa	PNEC = 0.188mg/L	PNEC = 0.71mg/kg	PNEC = 1.88mg/L	PNEC = 10mg/L	PNEC = 0.03mg/kg
nol		sediment dw			soil dw
124-68-5 (10-20)					
Iodine	PNEC = 18.13µg/L	PNEC = 3.99mg/kg		PNEC = 11mg/L	PNEC = 5.95mg/kg
7553-56-2 (5-10)		sediment dw			soil dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Methyl alcohol	PNEC = 2.08mg/L	PNEC = 7.7mg/kg			
67-56-1 (25-50)		sediment dw			
Chloroform	PNEC = 0.015mg/L	PNEC = 0.09mg/kg			
67-66-3 (10-20)		sediment dw			
2-Amino-2-methyl-1-propa	PNEC =	PNEC =			
nol	0.0188mg/L	0.071mg/kg			
124-68-5 (10-20)		sediment dw			
Iodine	PNEC = 60.01µg/L	PNEC =			
7553-56-2 (5-10)		20.22mg/kg			
		sediment dw			

8.2. Exposure controls

Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

ſ	Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
-	Viton (R)	See manufacturers	-	EN 374	(minimum requirement)
1		recommendations			

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to

EN371

Aqualine™ Electrolyte A (Anolyte for general use)

Revision Date 17-Jul-2025

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water

system.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance

Odor Alcohol-like No data available **Odor Threshold** Melting Point/Range No data available **Softening Point** No data available **Boiling Point/Range** No information available

On basis of test data Flammability (liquid) Highly flammable

Not applicable Flammability (solid, gas) Liquid

No data available **Explosion Limits**

10 °C / 50 °F **Flash Point** Method - No information available

Autoignition Temperature No data available No data available **Decomposition Temperature** pН No information available Viscosity No data available Water Solubility Partially soluble Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

log Pow Component Methyl alcohol -0.74 Chloroform 2 2-Amino-2-methyl-1-propanol -0.63 Iodine 2.49

No data available **Vapor Pressure**

Density / Specific Gravity 1.16

Bulk Density Not applicable Liquid **Vapor Density** No data available (Air = 1.0)

Particle characteristics Not applicable (liquid)

9.2. Other information

Vapors may form explosive mixtures with air **Explosive Properties**

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

Aqualine™ Electrolyte A (Anolyte for general use)

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

Revision Date 17-Jul-2025

sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases. Finely powdered metals.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Nitrogen oxides (NOx). Chlorine. Hydrogen

halides. Formaldehyde.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral Category 3
Dermal Category 3
Inhalation Category 3

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h
Chloroform	LD50 = 908 mg/kg (rat) LD50 = 695 mg/kg (Rat) LD50 = 450 mg/kg (Rat)	LD50 > 20 g/kg(Rabbit)	LC50 = 10.5 mg/L (Rat) 4 h
2-Amino-2-methyl-1-propanol	LD50 = 2900 mg/kg (Rat)	>2000 mg/kg(Rabbit)	-
2,4,6-Collidine	400 mg/kg (Rat)	1000 mg/kg (Guinea Pig)	-
Sulfur dioxide	-	-	Per CGA P-20: 2500 ppm/1hr (Rat)
lodine	315 mg/kg (Rat)	1425 mg/kg (Rabbit)	4.588 mg/L 4h (Rat)
Toluene-4-sulfonic acid monohydrate	2570 mg/kg (Rat)	-	-

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory SkinNo data available
No data available

Component	Test method	Test species	Study result
Methyl alcohol	OECD Test Guideline 406	guinea pig	non-sensitising
67-56-1 (25-50)	Guinea Pig Maximisation Test		_
	(GPMT)		
Iodine	OECD Test Guideline 429	mouse	non-sensitising
7553-56-2 (5-10)	Local Lymph Node Assay		_

Aqualine™ Electrolyte A (Anolyte for general use)

Revision Date 17-Jul-2025

No data available (e) germ cell mutagenicity;

(f) carcinogenicity; Category 2

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Chloroform				Group 2B

(a) reproductive toxicity: Category 2

Component	Test method	Test species / Duration	Study result
Methyl alcohol	OECD Test Guideline 416	Rat / Inhalation	NOAEC =
67-56-1 (25-50)		2 Generation	1.3 mg/l (air)

Category 1 (h) STOT-single exposure;

Optic nerve, Respiratory system, Central nervous system (CNS). Results / Target organs

(i) STOT-repeated exposure; Category 1

Route of exposure

Inhalation

Liver, Kidney, Thyroid. **Target Organs**

No data available (i) aspiration hazard;

delayed

Symptoms / effects,both acute and Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic **Ecotoxicity effects**

environment. The product contains following substances which are hazardous for the

environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Methyl alcohol	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 > 10000 mg/L 24h	
Chloroform	LC50: = 300 mg/L, 96h static (Poecilia reticulata) LC50: = 18 mg/L, 96h flow-through (Lepomis macrochirus) LC50: = 18 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: = 71 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 28.9 mg/L/48h	EC50 = 560 mg/L/48h

Aqualine™ Electrolyte A (Anolyte for general use)

Revision Date 17-Jul-2025

2-Amino-2-methyl-1-propanol	LC50: = 190 mg/L, 96h static	EC50: = 193 mg/L, 48h	EC50: = 520 mg/L, 72h
	(Lepomis macrochirus)	(Daphnia magna)	(Desmodesmus subspicatus)
lodine	LC50 = 1.67 mg/L 96h	EC50 = 0.55 mg/L 48h	EC50 = 0.13 mg/L 72h

Component	Microtox	M-Factor
Methyl alcohol	EC50 = 39000 mg/L 25 min	
	EC50 = 40000 mg/L 15 min	
	EC50 = 43000 mg/L 5 min	
Chloroform	Photobacterium phosphoreum: EC50 = 520 mg/L/5	
	min	
	Photobacterium phosphoreum: EC50 = 670	
	mg/L/15 min	
	Photobacterium phosphoreum: EC50 = 670	
	mg/L/30min	
2-Amino-2-methyl-1-propanol	EC50: = 342.9 mg/L, 3 h (Activated Sludge) OECD	
	209	
Iodine	EC50 = 280 mg/L 3h	1

12.2. Persistence and degradability Not applicable for mixtures

	12121 1 CICIOTO CONTRO	
Component		Degradability
	Methyl alcohol	DT50 ~ 17.2d
	67-56-1 (25-50)	>94% after 20d

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste

water treatment plants.

12.3. Bioaccumulative potential There is no data for this product; Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Methyl alcohol	-0.74	<10 dimensionless
Chloroform	2	1.4 - 13 dimensionless
2-Amino-2-methyl-1-propanol	-0.63	<1 dimensionless
lodine	2.49	No data available

12.4. Mobility in soil Contains organic solvents. Will likely be mobile in the environment due to its volatility.

Disperses rapidly in air

12.5. Results of PBT and vPvB

assessment

No data available for assessment.

12.6. Endocrine disrupting

properties

Endocrine Disruptor Information This product d

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

Aqualine™ Electrolyte A (Anolyte for general use)

Revision Date 17-Jul-2025

empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but

application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the

application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH

and harm aquatic organisms.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN1992

14.2. UN proper shipping name Technical Shipping NameFLAMMABLE LIQUID, TOXIC, N.O.S.
Contains methanol, chloroform

14.3. Transport hazard class(es) 3
Subsidiary Hazard Class 6.1
14.4. Packing group II

ADR

14.1. UN number UN1992

14.2. UN proper shipping name FLAMMABLE LIQUID, TOXIC, N.O.S.

Technical Shipping Name Contains methanol, chloroform

14.3. Transport hazard class(es)3Subsidiary Hazard Class6.114.4. Packing groupII

<u>IATA</u>

14.1. UN number UN1992

14.2. UN proper shipping name FLAMMABLE LIQUID, TOXIC, N.O.S.

Technical Shipping Name Contains methanol, chloroform

14.3. Transport hazard class(es)3Subsidiary Hazard Class6.114.4. Packing groupII

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

<u>14.7. Maritime transport in bulk</u> Not applicable, packaged goods according to IMO instruments

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Aqualine™ Electrolyte A (Anolyte for general use)

Revision Date 17-Jul-2025

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Methyl alcohol	67-56-1	200-659-6	-	-	X	X	KE-23193	X	Х
Chloroform	67-66-3	200-663-8	-	-	Х	X	X	X	Х
2-Amino-2-methyl-1-propanol	124-68-5	204-709-8	-	-	Х	Х	KE-01473	X	Х
2,4,6-Collidine	108-75-8	203-613-3	-	-	Х	X	-	X	Х
Sulfur dioxide	7446-09-5	231-195-2	-	-	Х	X	KE-32567	X	Х
lodine	7553-56-2	231-442-4	-	-	Х	Х	KE-21023	Х	-
Toluene-4-sulfonic acid	6192-52-5	-	-	-	Х	Х	-	-	-
monohydrate									

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Methyl alcohol	67-56-1	X	ACTIVE	Х	-	Χ	Х	Х
Chloroform	67-66-3	Х	ACTIVE	Х	-	Х	Х	Х
2-Amino-2-methyl-1-propanol	124-68-5	Х	ACTIVE	Х	-	Х	Х	Х
2,4,6-Collidine	108-75-8	Х	ACTIVE	Х	-	Х	Х	Х
Sulfur dioxide	7446-09-5	Х	ACTIVE	Х	-	Х	Х	Х
lodine	7553-56-2	Х	ACTIVE	Х	-	X	Х	Х
Toluene-4-sulfonic acid monohydrate	6192-52-5	-	-	-	-	Х	Х	Х

Legend: X - Listed '-' - Not Listed **KECL** - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl alcohol	67-56-1	-	Use restricted. See entry 69. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-
Chloroform	67-66-3	-	Use restricted. See item 32. (see http://eur-lex.europa.eu/Le xUriServ/LexUriServ.do?ur i=CELEX:32006R1907:EN: NOT for restriction details)	
2-Amino-2-methyl-1-propanol	124-68-5	-	Use restricted. See entry 75. (see link for restriction details)	-
2,4,6-Collidine	108-75-8	-	-	-
Sulfur dioxide	7446-09-5	-	Use restricted. See entry 75. (see link for restriction details)	-
lodine	7553-56-2	-	Use restricted. See entry 75. (see link for restriction details)	-
Toluene-4-sulfonic acid monohydrate	6192-52-5	-	- '	-

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Methyl alcohol	67-56-1	500 tonne	5000 tonne
Chloroform	67-66-3	Not applicable	Not applicable
2-Amino-2-methyl-1-propano	124-68-5	Not applicable	Not applicable
2,4,6-Collidine	108-75-8	Not applicable	Not applicable
Sulfur dioxide	7446-09-5	Not applicable	Not applicable
lodine	7553-56-2	Not applicable	Not applicable
Toluene-4-sulfonic acid monohydrate	6192-52-5	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Component	ANNEX I - PART 1 List of chemicals subject to export notification procedure (referred to in Article 8)	ANNEX I - PART 2 List of chemicals qualifying for PIC notification (referred to in Article 11)	ANNEX I - PART 3 List of chemicals subject to the PIC procedure (referred to in Articles 13 and 14)
Chloroform 67-66-3 (10-20)	b — ban (for the category or categories concerned) b — ban (for the category or categories concerned)	-	-
	i(2) — industrial chemical for public		

https://eur-lex.europa.eu/legal-content/EN/TXT/?uri=CELEX%3A32012R0649&qid=1604065742303.

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification Water endangering class = 3 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Methyl alcohol	WGK 2	Class I: 20 mg/m3 (Massenkonzentration)
Chloroform	WGK 3	Class I: 20 mg/m3 (Massenkonzentration)
2-Amino-2-methyl-1-propanol	WGK1	
Sulfur dioxide	WGK1	
lodine	WGK2	

Component	France - INRS (Tables of occupational diseases)		
Methyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84		
Chloroform	Tableaux des maladies professionnelles (TMP) - RG 12		

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Methyl alcohol	Prohibited and Restricted	Group I	
67-56-1 (25-50)	Substances		
Chloroform	Prohibited and Restricted		Annex I - industrial chemical
67-66-3 (10-20)	Substances		
Iodine	Prohibited and Restricted		
7553-56-2 (5-10)	Substances		
Toluene-4-sulfonic acid monohydrate	Prohibited and Restricted		
6192-52-5 (0.1-1)	Substances		

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H301 - Toxic if swallowed

H311 - Toxic in contact with skin

H331 - Toxic if inhaled

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H370 - Causes damage to organs

H351 - Suspected of causing cancer

H361d - Suspected of damaging the unborn child

H372 - Causes damage to organs through prolonged or repeated exposure

H225 - Highly flammable liquid and vapor

H226 - Flammable liquid and vapor

H302 - Harmful if swallowed

H312 - Harmful in contact with skin

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H400 - Very toxic to aquatic life

H412 - Harmful to aquatic life with long lasting effects

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

> **ENCS** - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative

Aqualine™ Electrolyte A (Anolyte for general use)

Revision Date 17-Jul-2025

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air

Transport Association

MARPOL - International Convention for the Prevention of Pollution from

Shins

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data **Health Hazards** Calculation method **Environmental hazards** Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

05-Jan-2011 **Creation Date** 17-Jul-2025 **Revision Date Revision Summary** 2, 3.

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet