

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 13-Sep-2010

Revision Date 13-Oct-2023

**Revision Number** 9

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product Description:
Cat No. :
Synonyms
CAS No
EC No
Molecular Formula
REACH registration number

<u>3-Methyl-1-butanol</u> BP1150-500 Isoamyl alcohol; Isopentyl alcohol 123-51-3 204-633-5 C5 H12 O 01-2119493725-26

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Sector of use	Laboratory chemicals. SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites
Product category	PC21 - Laboratory chemicals
Process categories	PROC15 - Use as a laboratory reagent
Environmental release category	ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)
Uses advised against	No Information available

#### 1.3. Details of the supplier of the safety data sheet

Company

UK entity/business name Fisher Scientific UK Bishop Meadow Road, Loughborough, Leicestershire LE11 5RG, United Kingdom

#### EU entity/business name

Thermo Fisher Scientific Janssen Pharmaceuticalaan 3a, 2440 Geel, Belgium

E-mail address

begel.sdsdesk@thermofisher.com

#### 1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

## **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

#### 3-Methyl-1-butanol

#### Revision Date 13-Oct-2023

#### Physical hazards

Flammable liquids

#### Health hazards

Acute Inhalation Toxicity - Vapors Skin Corrosion/Irritation Serious Eye Damage/Eye Irritation Specific target organ toxicity - (single exposure)

#### **Environmental hazards**

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

#### 2.2. Label elements



Signal Word

Warning

#### **Hazard Statements**

- H226 Flammable liquid and vapor
- H332 Harmful if inhaled
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H335 May cause respiratory irritation
- EUH066 Repeated exposure may cause skin dryness or cracking

#### **Precautionary Statements**

- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P302 + P352 IF ON SKIN: Wash with plenty of soap and water
- P332 + P313 If skin irritation occurs: Get medical advice/attention
- P337 + P313 If eye irritation persists: Get medical advice/attention
- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

#### 2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Category 3 (H226)

Category 4 (H332) Category 2 (H315) Category 2 (H319) Category 3 (H335)

#### 3-Methyl-1-butanol

#### 3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Isoamyl alcohol	123-51-3	EEC No. 204-633-5	<=100	Flam Liq. 3 (H226) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335) (EUH066)

REACH registration number	01-2119493725-26

Full text of Hazard Statements: see section 16

## **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of first aid measures

General Advice	If symptoms persist, call a physician.			
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.			
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention.			
Ingestion	Do NOT induce vomiting. Get medical attention.			
Inhalation	Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention. If not breathing, give artificial respiration.			
Self-Protection of the First Aider	Use personal protective equipment as required.			
4.2. Most important symptoms and	effects, both acute and delayed			
	Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting			
4.3. Indication of any immediate medical attention and special treatment needed				

Notes to Physician	Treat symptomatically. Symptoms may be delayed.
--------------------	---

## **SECTION 5: FIREFIGHTING MEASURES**

#### 5.1. Extinguishing media

#### Suitable Extinguishing Media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

## Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

#### 5.2. Special hazards arising from the substance or mixture

#### 3-Methyl-1-butanol

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors.

#### **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>).

#### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

#### 6.2. Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

#### 6.3. Methods and material for containment and cleaning up

Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

#### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

#### **SECTION 7: HANDLING AND STORAGE**

#### 7.1. Precautions for safe handling

Use only under a chemical fume hood. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Use only non-sparking tools.

#### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice.

#### 7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

#### Technical Rules for Hazardous Substances (TRGS) 510 Class 3 Storage Class (LGK) (Germany)

#### 7.3. Specific end use(s)

Use in laboratories

### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### 8.1. Control parameters

#### **Exposure limits**

List source(s): **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE -** 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Isoamyl alcohol	STEL: 125 ppm 15 min		TWA: 5 ppm 8 hr.
	STEL: 458 mg/m <sup>3</sup> 15 min		TWA: 18 mg/m <sup>3</sup> 8 hr.
	TWA: 100 ppm 8 hr		STEL: 10 mg/m <sup>3</sup> 15 min
	TWA: 366 mg/m <sup>3</sup> 8 hr		STEL: 37 ppm 15 min

#### **Biological limit values**

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

#### Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Isoamyl alcohol 123-51-3 ( <=100 )	DNEL = 292mg/m <sup>3</sup>		DNEL = 73.16mg/m <sup>3</sup>	

#### Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment		Microorganisms in sewage treatment	Soil (Agriculture)
Isoamyl alcohol 123-51-3 ( <=100 )	PNEC = 0.12mg/L	PNEC = 0.496mg/kg sediment dw	PNEC = 1.2mg/L	PNEC = 37mg/L	PNEC = 0.0287mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Isoamyl alcohol	PNEC = 0.012mg/L	PNEC =			
123-51-3(<=100)		0.0496mg/kg			
		sediment dw			

#### 8.2. Exposure controls

#### Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment Eye Protection	Goggles (European standard - EN 166)
Hand Protection	Protective gloves

Revision Date 13-Oct-2023

3-Methyl-1-butanol	
--------------------	--

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	See manufacturers	-	EN 374	(minimum requirement)
Viton (R)	recommendations			
Skin and body prot	ection Long sle	eved clothing.		

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly
Large scale/emergency use	Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced <b>Recommended Filter type:</b> Organic gases and vapours filter Type A Brown conforming to EN14387
Small scale/Laboratory use	Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. <b>Recommended half mask:-</b> Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141 When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls No information available.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

#### 9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Clear	
Odor	Characteristic	
Odor Threshold	No data available	
Melting Point/Range	-117 °C / -178.6 °F	
Softening Point	No data available	
Boiling Point/Range	130 - 132 °C / 266 - 269.6 °F	760 mm HG
Flammability (liquid)	Flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 1.0 Vol%	
	Upper 8 Vol%	
Flash Point	45 °C / 113 °F	Method - No information available
Autoignition Temperature	365 - °C / 689 - °F	
Decomposition Temperature	335 °C	
pH	6.5	25 g/l aq.sol
Viscosity	4.3 mPa s at 20 °C	
Water Solubility	25 g/L (20°C)	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/wate	er)	
Component	log Pow	
Isoamyl alcohol	1.35	
Vapor Pressure	4 hPa @ 20 °C	
Density / Specific Gravity	0.807-0.811	
Bulk Density	Not applicable	Liquid

Revision Date 13-Oct-2023

3-Methyl-1-butanol

Vapor Density Particle characteristics 3.04 (Air = 1.0) Not applicable (liquid) (Air = 1.0)

9.2. Other information

Molecular Formula Molecular Weight Explosive Properties C5 H12 O 88.15 explosive air/vapour mixtures possible

## SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization<br/>Hazardous ReactionsHazardous polymerization does not occur.<br/>None under normal processing.10.4. Conditions to avoidHazardous polymerization does not occur.<br/>None under normal processing.

- Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.
- 10.5. Incompatible materials

Strong oxidizing agents. Metals. Alkali metals. Halogens. Acids. Acid anhydrides. Acid chlorides. Isocyanates.

#### 10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

**SECTION 11: TOXICOLOGICAL INFORMATION** 

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Product Information** 

(a) acute toxicity;

OralBased on available data, the classification criteria are not metDermalBased on available data, the classification criteria are not metInhalationCategory 4

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isoamyl alcohol	LD50 = 5770 mg/kg (Rat)	LD50 = 3250 mg/kg (Rabbit)	LC50 > 2000 ppm (Rat) 8 h

(b) skin corrosion/irritation;	Category 2
--------------------------------	------------

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization; Respiratory

Based on available data, the classification criteria are not met

Skin	Based on available data, the classification criteria are not met
(e) germ cell mutagenicity;	Based on available data, the classification criteria are not met
(f) carcinogenicity;	Based on available data, the classification criteria are not met
	There are no known carcinogenic chemicals in this product
(g) reproductive toxicity;	Based on available data, the classification criteria are not met
(h) STOT-single exposure;	Category 3
Results / Target organs	Respiratory system.
(i) STOT-repeated exposure;	Based on available data, the classification criteria are not met
Target Organs	None known.
(j) aspiration hazard;	Based on available data, the classification criteria are not met
Other Adverse Effects	Tumorigenic effects have been reported in experimental animals.
Symptoms / effects,both acute and delayed	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

#### 11.2. Information on other hazards

**Endocrine Disrupting Properties** 

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## **SECTION 12: ECOLOGICAL INFORMATION**

#### 12.1. Toxicity Ecotoxicity effects

3-Methyl-1-butanol

This product contains the following substance(s) which are hazardous for the environment. .

Component	Freshwater Fish	Water Flea	Freshwater Algae
Isoamyl alcohol	LC50 96 h 700 mg/L (rainbow trout)	EC50: = 260 mg/L, 48h (Daphnia magna)	EC50: = 181 mg/L, 96h (Desmodesmus subspicatus) EC50: = 493 mg/L, 72h (Desmodesmus subspicatus)

Component	Microtox	M-Factor
Isoamyl alcohol	EC50 = 2500 mg/L 17 h	

#### 12.2. Persistence and degradability Readily biodegradable

**Persistence** Soluble in water, Persistence is unlikely, based on information available.

#### 12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Isoamyl alcohol	1.35	No data available

3-Methyl-1-butanol	Revision Date 13-Oct-2023
12.4. Mobility in soil	The product is water soluble, and may spread in water systems . Will likely be mobile in the environment due to its water solubility. Highly mobile in soils
12.5. Results of PBT and vPvB assessment	Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).
<u>12.6. Endocrine disrupting</u> properties Endocrine Disruptor Information	This product does not contain any known or suspected endocrine disruptors
<u>12.7. Other adverse effects</u> Persistent Organic Pollutant	This product does not contain any known or suspected substance

Ozone Depletion Potential

This product does not contain any known of suspected substance

## **SECTION 13: DISPOSAL CONSIDERATIONS**

#### 13.1. Waste treatment methods

Waste from Residues/Unused Products	Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.
Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
European Waste Catalogue (EWC)	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
Other Information	Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations.

## **SECTION 14: TRANSPORT INFORMATION**

#### IMDG/IMO

<u>14.1. UN number</u> <u>14.2. UN proper shipping name</u> <u>14.3. Transport hazard class(es)</u> <u>14.4. Packing group</u>	UN1105 PENTANOLS 3 III
ADR <u>14.1. UN number</u> <u>14.2. UN proper shipping name</u> <u>14.3. Transport hazard class(es)</u> <u>14.4. Packing group</u>	UN1105 PENTANOLS 3 III
IATA 14.1. UN number 14.2. UN proper shipping name	UN1105 PENTANOLS

14.2. UN proper shipping name	PENTA
14.3. Transport hazard class(es)	3

3-Methyl-1-butanol

#### 14.4. Packing group

**14.5. Environmental hazards** No hazards identified

14.6. Special precautions for user No special precautions required.

Ш

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

## **SECTION 15: REGULATORY INFORMATION**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Isoamyl alcohol	123-51-3	204-633-5	-	-	Х	Х	KE-23575	Х	Х

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Isoamyl alcohol	123-51-3	Х	ACTIVE	Х	-	Х	Х	Х

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

Not applicable

#### Authorisation/Restrictions according to EU REACH

REACH (1907/2006) -CAS No REACH (1907/2006) -**REACH Regulation (EC** Component Annex XIV - Substances Annex XVII - Restrictions 1907/2006) article 59 -Subject to Authorization on Certain Dangerous Candidate List of Substances of Very High Substances Concern (SVHC) Isoamyl alcohol 123-51-3 -

#### Seveso III Directive (2012/18/EC)

ſ	Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Repor	
			Notification	Requirements	
Γ	Isoamyl alcohol	123-51-3	Not applicable	Not applicable	

## Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

#### Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

#### **National Regulations**

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

#### WGK Classification

See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Isoamyl alcohol	WGK1	

Component	France - INRS (Tables of occupational diseases)
Isoamyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84

#### 15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

#### **SECTION 16: OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3

H226 - Flammable liquid and vapor

H332 - Harmful if inhaled

H315 - Causes skin irritation

H335 - May cause respiratory irritation

EUH066 - Repeated exposure may cause skin dryness or cracking

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

H319 - Causes serious eye irritation

#### Legend

CAS - Chemical Abstracts Service	TSCA - United States Toxic Substances Control Act Section 8(b)
EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances IECSC - Chinese Inventory of Existing Chemical Substances	Substances List ENCS - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances
<b>KECL</b> - Korean Existing and Evaluated Chemical Substances	NZIOC - New Zealand Inventory of Chemicals
WEL - Workplace Exposure Limit ACGIH - American Conference of Governmental Industrial Hygienists DNEL - Derived No Effect Level RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50% NOEC - No Observed Effect Concentration PBT - Persistent, Bioaccumulative, Toxic	<ul> <li>TWA - Time Weighted Average</li> <li>IARC - International Agency for Research on Cancer</li> <li>Predicted No Effect Concentration (PNEC)</li> <li>LD50 - Lethal Dose 50%</li> <li>EC50 - Effective Concentration 50%</li> <li>POW - Partition coefficient Octanol:Water</li> <li>vPvB - very Persistent, very Bioaccumulative</li> </ul>
ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code OECD - Organisation for Economic Co-operation and Development BCF - Bioconcentration factor Key literature references and sources for data https://echa.europa.eu/information-on-chemicals	ICAO/IATA - International Civil Aviation Organization/International Air Transport Association MARPOL - International Convention for the Prevention of Pollution from Ships ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

#### **Training Advice**

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

#### 3-Methyl-1-butanol

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical incident response training.

Creation Date	13-Sep-2010
Revision Date	13-Oct-2023
Revision Summary	Not applicable.

## This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

## End of Safety Data Sheet