

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product Description: Diethylaluminium iodide, 0.9M solution in toluene  
 Cat No. : 381160000; 381161000; 381168000  
 Synonyms DEAI  
 Molecular Formula C<sub>4</sub> H<sub>10</sub> Al I

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.  
 Uses advised against No Information available

### 1.3. Details of the supplier of the safety data sheet

#### Company

**UK entity/business name**  
 Fisher Scientific UK  
 Bishop Meadow Road,  
 Loughborough, Leicestershire LE11 5RG, United Kingdom

**EU entity/business name**  
 Thermo Fisher Scientific  
 Janssen Pharmaceuticaaan 3a, 2440 Geel, Belgium

E-mail address begel.sdsdesk@thermofisher.com

### 1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11  
 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99  
**CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

#### CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

##### Physical hazards

Flammable liquids	Category 2 (H225)
Substances/mixtures which, in contact with water, emit flammable gases	Category 1 (H260)
Pyrophoric liquids	Category 1 (H250)

##### Health hazards

# SAFETY DATA SHEET

Diethylaluminium iodide, 0.9M solution in toluene

Revision Date 09-Feb-2024

Aspiration Toxicity	Category 1 (H304)
Skin Corrosion/Irritation	Category 1 A (H314)
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Reproductive Toxicity	Category 2 (H361d)
Specific target organ toxicity - (single exposure)	Category 3 (H336)
Specific target organ toxicity - (repeated exposure)	Category 2 (H373)
<b>Environmental hazards</b>	
Chronic aquatic toxicity	Category 3 (H412)

Full text of Hazard Statements: see section 16

## 2.2. Label elements



Signal Word

Danger

## Hazard Statements

- H225 - Highly flammable liquid and vapor
- H250 - Catches fire spontaneously if exposed to air
- H260 - In contact with water releases flammable gases which may ignite spontaneously
- H304 - May be fatal if swallowed and enters airways
- H314 - Causes severe skin burns and eye damage
- H336 - May cause drowsiness or dizziness
- H361d - Suspected of damaging the unborn child
- H373 - May cause damage to organs through prolonged or repeated exposure
- H412 - Harmful to aquatic life with long lasting effects
- EUH014 - Reacts violently with water

## Precautionary Statements

- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P222 - Do not allow contact with air
- P231 + P232 - Handle and store contents under inert gas. Protect from moisture
- P280 - Wear protective gloves/protective clothing/eye protection/face protection
- P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
- P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P310 - Immediately call a POISON CENTER or doctor/physician

## 2.3. Other hazards

- Reacts violently with water
- Toxic to terrestrial vertebrates
- This product does not contain any known or suspected endocrine disruptors

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

# SAFETY DATA SHEET

Diethylaluminium iodide, 0.9M solution in toluene

Revision Date 09-Feb-2024

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Toluene	108-88-3	203-625-9	80	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Repr. 2 (H361d) STOT RE 2 (H373) Aquatic Chronic 3 (H412)
Aluminum, diethylido-	2040-00-8	EEC No. 218-032-0	19.5-20.5	Pyr. Liq. 1 (H250) Water-react. 1 (H260) Skin Corr. 1A (H314) [EUH014]

Full text of Hazard Statements: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

<b>General Advice</b>	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
<b>Ingestion</b>	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
<b>Inhalation</b>	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. Risk of serious damage to the lungs (by aspiration).
<b>Self-Protection of the First Aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

### 4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes to Physician** Treat symptomatically. Symptoms may be delayed.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

# SAFETY DATA SHEET

Diethylaluminium iodide, 0.9M solution in toluene

Revision Date 09-Feb-2024

## Suitable Extinguishing Media

Dry chemical. Water mist may be used to cool closed containers. CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam.

## Extinguishing media which must not be used for safety reasons

Water.

## 5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

## Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Hydrogen, Burning produces obnoxious and toxic fumes, Ethane.

## 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges. DO NOT GET WATER on spilled substance or inside containers

### 6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

### 6.3. Methods and material for containment and cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Do not get in eyes, on skin, or on clothing. Wear personal protective equipment/face protection. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. Handle under an inert atmosphere. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

## Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep from any possible contact with water. Flammables area. Keep under nitrogen. Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area. Keep away from heat, sparks and flame. Keep away from water or moist air. Store

# SAFETY DATA SHEET

Diethylaluminium iodide, 0.9M solution in toluene

Revision Date 09-Feb-2024

under an inert atmosphere. Protect from moisture.

**Technical Rules for Hazardous Substances (TRGS) 510**      Class 4.2  
**Storage Class (LGK) (Germany)**

### 7.3. Specific end use(s)

Use in laboratories

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Toluene	STEL: 100 ppm 15 min STEL: 384 mg/m <sup>3</sup> 15 min TWA: 50 ppm 8 hr TWA: 191 mg/m <sup>3</sup> 8 hr Skin	TWA: 50 ppm (8hr) TWA: 192 mg/m <sup>3</sup> (8hr) STEL: 100 ppm (15min) STEL: 384 mg/m <sup>3</sup> (15min) Skin	TWA: 192 mg/m <sup>3</sup> 8 hr. TWA: 50 ppm 8 hr. STEL: 384 mg/m <sup>3</sup> 15 min STEL: 100 ppm 15 min Skin

#### Biological limit values

List source(s):

#### Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Oral)	Acute effects systemic (Oral)	Chronic effects local (Oral)	Chronic effects systemic (Oral)
Toluene 108-88-3 ( 80 )				8.13 mg/kg bw/day

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Toluene 108-88-3 ( 80 )				DNEL = 384mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Toluene 108-88-3 ( 80 )	DNEL = 384mg/m <sup>3</sup>	DNEL = 384mg/m <sup>3</sup>	DNEL = 192mg/m <sup>3</sup>	DNEL = 192mg/m <sup>3</sup>

#### Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Toluene 108-88-3 ( 80 )	PNEC = 0.68mg/L	PNEC = 16.39mg/kg sediment dw	PNEC = 0.68mg/L	PNEC = 13.61mg/L	PNEC = 2.89mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air

# SAFETY DATA SHEET

Diethylaluminium iodide, 0.9M solution in toluene

Revision Date 09-Feb-2024

Toluene 108-88-3 ( 80 )	PNEC = 0.68mg/L	PNEC = 16.39mg/kg sediment dw			
----------------------------	-----------------	-------------------------------------	--	--	--

## 8.2. Exposure controls

### Engineering Measures

Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

#### Eye Protection

Goggles (European standard - EN 166)

#### Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber Viton (R)	See manufacturers recommendations	-	EN 374	(minimum requirement)

#### Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

#### Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

#### Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

**Recommended Filter type:** low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387

#### Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

**Recommended half mask:-** Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141

When RPE is used a face piece Fit Test should be conducted

#### Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

#### Physical State

Liquid

#### Appearance

Clear

#### Odor

No information available

#### Odor Threshold

No data available

#### Melting Point/Range

No data available

#### Softening Point

No data available

#### Boiling Point/Range

No information available

# SAFETY DATA SHEET

Diethylaluminium iodide, 0.9M solution in toluene

Revision Date 09-Feb-2024

<b>Flammability (liquid)</b>	Highly flammable	Estimated
<b>Flammability (solid,gas)</b>	Not applicable	Liquid
<b>Explosion Limits</b>	No data available	
<b>Flash Point</b>	No information available	<b>Method -</b> No information available
<b>Autoignition Temperature</b>	No data available	
<b>Decomposition Temperature</b>	No data available	
<b>pH</b>	Not applicable	
<b>Viscosity</b>	No data available	
<b>Water Solubility</b>	Reacts violently with water	
<b>Solubility in other solvents</b>	No information available	
<b>Partition Coefficient (n-octanol/water)</b>		
<b>Component</b>	<b>log Pow</b>	
Toluene	2.73	
<b>Vapor Pressure</b>	No data available	
<b>Density / Specific Gravity</b>	No data available	
<b>Bulk Density</b>	Not applicable	Liquid
<b>Vapor Density</b>	No data available	(Air = 1.0)
<b>Particle characteristics</b>	Not applicable (liquid)	

## 9.2. Other information

<b>Molecular Formula</b>	C4 H10 Al I
<b>Molecular Weight</b>	212.01
<b>Explosive Properties</b>	Vapors may form explosive mixtures with air
<b>Substances/mixtures which, in contact with water, emit flammable gases</b>	Emitted gas ignites spontaneously Gas(es) = Ethane

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

Yes

### 10.2. Chemical stability

Moisture sensitive. Air sensitive.

### 10.3. Possibility of hazardous reactions

<b>Hazardous Polymerization</b>	No information available.
<b>Hazardous Reactions</b>	Reacts violently with water.

### 10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition. Exposure to air. Incompatible products. Exposure to moist air or water. Exposure to moisture.

### 10.5. Incompatible materials

Acids. Water. Alcohols.

### 10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Hydrogen. Burning produces obnoxious and toxic fumes. Ethane.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Product Information**

No acute toxicity information is available for this product

# SAFETY DATA SHEET

Diethylaluminium iodide, 0.9M solution in toluene

Revision Date 09-Feb-2024

**(a) acute toxicity;**

**Oral** Based on available data, the classification criteria are not met  
**Dermal** Based on available data, the classification criteria are not met  
**Inhalation** Based on available data, the classification criteria are not met

**Toxicology data for the components**

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Toluene	> 5000 mg/kg ( Rat )	12000 mg/kg ( Rabbit )	26700 ppm ( Rat ) 1 h

**(b) skin corrosion/irritation;** Category 1 A

**(c) serious eye damage/irritation;** Category 1

**(d) respiratory or skin sensitization;**

**Respiratory** No data available  
**Skin** No data available

**(e) germ cell mutagenicity;** No data available

**(f) carcinogenicity;** No data available

There are no known carcinogenic chemicals in this product

**(g) reproductive toxicity;  
Teratogenicity**

Category 2  
Teratogenic effects have occurred in experimental animals.

**(h) STOT-single exposure;**

Category 3

**Results / Target organs**

Central nervous system (CNS).

**(i) STOT-repeated exposure;**

Category 2

**Target Organs**

Neuropsychological effects, Eyes, Ears.

**(j) aspiration hazard;**

Category 1

**Other Adverse Effects**

The toxicological properties have not been fully investigated.

**Symptoms / effects,both acute and delayed**

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated.

**11.2. Information on other hazards**

**Endocrine Disrupting Properties**

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## SECTION 12: ECOLOGICAL INFORMATION

**12.1. Toxicity**

**Ecotoxicity effects**

The product contains following substances which are hazardous for the environment. Contains a substance which is: Harmful to aquatic organisms.



# SAFETY DATA SHEET

Diethylaluminium iodide, 0.9M solution in toluene

Revision Date 09-Feb-2024

Component	Freshwater Fish	Water Flea	Freshwater Algae
Toluene	50-70 mg/L LC50 96 h 5-7 mg/L LC50 96 h 15-19 mg/L LC50 96 h 28 mg/L LC50 96 h 12 mg/L LC50 96 h	EC50: = 11.5 mg/L, 48h (Daphnia magna) EC50: 5.46 - 9.83 mg/L, 48h Static (Daphnia magna)	EC50: = 12.5 mg/L, 72h static (Pseudokirchneriella subcapitata) EC50: > 433 mg/L, 96h (Pseudokirchneriella subcapitata)

Component	Microtox	M-Factor
Toluene	EC50 = 19.7 mg/L 30 min	

## 12.2. Persistence and degradability

**Persistence** Soluble in water, Persistence is unlikely, based on information available.  
**Degradability** Reacts with water.

Component	Degradability
Toluene 108-88-3 ( 80 )	86% (20d)

**Degradation in sewage treatment plant** Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants. Reacts violently with water.

**12.3. Bioaccumulative potential** Product does not bioaccumulate due to reaction with water

Component	log Pow	Bioconcentration factor (BCF)
Toluene	2.73	90

**12.4. Mobility in soil** Reacts violently with water Is not likely mobile in the environment. Highly mobile in soils

**12.5. Results of PBT and vPvB assessment** Reacts violently with water.

## 12.6. Endocrine disrupting properties

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors

## 12.7. Other adverse effects Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance  
This product does not contain any known or suspected substance

# SECTION 13: DISPOSAL CONSIDERATIONS

## 13.1. Waste treatment methods

**Waste from Residues/Unused Products** Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

**Contaminated Packaging** Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

**European Waste Catalogue (EWC)** According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

**Other Information** Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms. Do not let this chemical enter the environment.

# SAFETY DATA SHEET

Diethylaluminium iodide, 0.9M solution in toluene

Revision Date 09-Feb-2024

## SECTION 14: TRANSPORT INFORMATION

### IMDG/IMO

<b>14.1. UN number</b>	UN3399
<b>14.2. UN proper shipping name</b> Technical Shipping Name	ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE (DIETHYLALUMINUM IODIDE, TOLUENE)
<b>14.3. Transport hazard class(es)</b>	4.3
Subsidiary Hazard Class	3
<b>14.4. Packing group</b>	I

### ADR

<b>14.1. UN number</b>	UN3399
<b>14.2. UN proper shipping name</b> Technical Shipping Name	ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE (DIETHYLALUMINUM IODIDE, TOLUENE)
<b>14.3. Transport hazard class(es)</b>	4.3
Subsidiary Hazard Class	3
<b>14.4. Packing group</b>	I

### IATA

<b>14.1. UN number</b>	UN3399
<b>14.2. UN proper shipping name</b> Technical Shipping Name	ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE (DIETHYLALUMINUM IODIDE, TOLUENE)
<b>14.3. Transport hazard class(es)</b>	4.3
Subsidiary Hazard Class	3
<b>14.4. Packing group</b>	I

<b>14.5. Environmental hazards</b>	No hazards identified
<b>14.6. Special precautions for user</b>	No special precautions required.
<b>14.7. Maritime transport in bulk according to IMO instruments</b>	Not applicable, packaged goods

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Toluene	108-88-3	203-625-9	-	-	X	X	KE-33936	X	X
Aluminum, diethylo-	2040-00-8	218-032-0	-	-	-	-	-	-	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Toluene	108-88-3	X	ACTIVE	X	-	X	X	X
Aluminum, diethylo-	2040-00-8	X	ACTIVE	-	X	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) -	REACH (1907/2006) -	REACH Regulation (EC
-----------	--------	---------------------	---------------------	----------------------

# SAFETY DATA SHEET

Diethylaluminium iodide, 0.9M solution in toluene

Revision Date 09-Feb-2024

		Annex XIV - Substances Subject to Authorization	Annex XVII - Restrictions on Certain Dangerous Substances	1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Toluene	108-88-3	-	Use restricted. See item 48. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Aluminum, diethylido-	2040-00-8	-	-	-

## REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

## Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Toluene	108-88-3	Not applicable	Not applicable
Aluminum, diethylido-	2040-00-8	Not applicable	Not applicable

## Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

## Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

## National Regulations

**UK** - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

## WGK Classification

Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Toluene	WGK3	
Aluminum, diethylido-	WGK1	

Component	France - INRS (Tables of occupational diseases)
Toluene	Tableaux des maladies professionnelles (TMP) - RG 4bis, RG 84

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Toluene 108-88-3 ( 80 )	Prohibited and Restricted Substances	Group I	

# SAFETY DATA SHEET

Diethylaluminium iodide, 0.9M solution in toluene

Revision Date 09-Feb-2024

## 15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3

H250 - Catches fire spontaneously if exposed to air  
H260 - In contact with water releases flammable gases which may ignite spontaneously  
H304 - May be fatal if swallowed and enters airways  
H314 - Causes severe skin burns and eye damage  
H318 - Causes serious eye damage  
H336 - May cause drowsiness or dizziness  
H361d - Suspected of damaging the unborn child  
H373 - May cause damage to organs through prolonged or repeated exposure  
H412 - Harmful to aquatic life with long lasting effects  
EUH014 - Reacts violently with water  
H225 - Highly flammable liquid and vapor  
H315 - Causes skin irritation

### Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration

**PBT** - Persistent, Bioaccumulative, Toxic

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer  
Predicted No Effect Concentration (PNEC)

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**POW** - Partition coefficient Octanol:Water

**vPvB** - very Persistent, very Bioaccumulative

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

**Key literature references and sources for data**

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (Volatile Organic Compound)

### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

**Physical hazards** On basis of test data

**Health Hazards** Calculation method

**Environmental hazards** Calculation method

### Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

**Creation Date** 17-Sep-2014

**Revision Date** 09-Feb-2024

**Revision Summary** Not applicable.

# SAFETY DATA SHEET

Diethylaluminium iodide, 0.9M solution in toluene

Revision Date 09-Feb-2024

---

**This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**