

according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended

Creation Date 03-Dec-2010 Revision Date 25-Jan-2024 Revision Number 3

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

## 1.1. Product identifier

Product Description: <u>Di-n-butyl ether</u>

 Cat No.:
 A16305

 Synonyms
 n-Butyl ether

 Index No
 603-054-00-9

 CAS No
 142-96-1

 EC No
 205-575-3

 Molecular Formula
 C8 H18 O

REACH registration number -

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

#### 1.3. Details of the supplier of the safety data sheet

Company

Avocado Research Chemicals Ltd. (Part of Thermo Fisher Scientific)

Shore Road, Heysham Lancashire, LA3 2XY, United Kingdom

Office Tel: +44 (0) 1524 850506 Office Fax: +44 (0) 1524 850608

**E-mail address** begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

# **SECTION 2: HAZARDS IDENTIFICATION**

## 2.1. Classification of the substance or mixture

## CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

## **Physical hazards**

Flammable liquids Category 3 (H226)

ALFAAA16305

Di-n-butyl ether Revision Date 25-Jan-2024

Health hazards

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Specific target organ toxicity - (single exposure)

Category 2 (H315)

Category 2 (H319)

Category 3 (H335)

**Environmental hazards** 

Chronic aquatic toxicity Category 3 (H412)

Full text of Hazard Statements: see section 16

#### 2.2. Label elements



#### Signal Word

#### Warning

## **Hazard Statements**

H226 - Flammable liquid and vapor

H319 - Causes serious eye irritation

H412 - Harmful to aquatic life with long lasting effects

H335 - May cause respiratory irritation

H315 - Causes skin irritation

#### **Precautionary Statements**

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P273 - Avoid release to the environment

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

#### 2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

This product does not contain any known or suspected endocrine disruptors

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

## 3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Butyl ether	142-96-1	EEC No. 205-575-3	>95	Flam. Liq. 3 (H226) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335) Aquatic Chronic 3 (H412)

Di-n-butyl ether Revision Date 25-Jan-2024

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Butyl ether	STOT SE 3 (H335) :: C>=10%	-	-

REACH registration number	-
---------------------------	---

Full text of Hazard Statements: see section 16

# **SECTION 4: FIRST AID MEASURES**

#### 4.1. Description of first aid measures

General Advice If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Get medical attention.

**Ingestion** Clean mouth with water and drink afterwards plenty of water.

**Inhalation** Remove to fresh air. Get medical attention. If not breathing, give artificial respiration.

**Self-Protection of the First Aider** Use personal protective equipment as required.

## 4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness,

nausea and vomiting

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes to Physician** Treat symptomatically. Symptoms may be delayed.

## **SECTION 5: FIREFIGHTING MEASURES**

## 5.1. Extinguishing media

#### **Suitable Extinguishing Media**

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons

No information available.

#### 5.2. Special hazards arising from the substance or mixture

Flammable. May form explosive peroxides. Risk of ignition. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Keep product and empty container away from heat and sources of ignition. Thermal decomposition can lead to release of irritating gases and vapors. Vapors may form explosive mixtures with air.

#### **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO2).

## 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

#### 6.2. Environmental precautions

Should not be released into the environment. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information. Avoid release to the environment. Collect spillage.

## 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

#### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

## 7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Ensure adequate ventilation. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

#### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice.

## 7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Store under an inert atmosphere.

Technical Rules for Hazardous Substances (TRGS) 510 Class 3 Storage Class (LGK) (Germany)

## 7.3. Specific end use(s)

Use in laboratories

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

# 8.1. Control parameters

#### **Exposure limits**

List source(s):

## **Biological limit values**

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Di-n-butyl ether Revision Date 25-Jan-2024

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Butyl ether 142-96-1 ( >95 )				DNEL = 4mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Butyl ether 142-96-1 ( >95 )				DNEL = 13mg/m <sup>3</sup>

## **Predicted No Effect Concentration (PNEC)**

See values below.

Component	Fresh water	Fresh water	Water Intermittent	Microorganisms in	Soil (Agriculture)
		sediment		sewage treatment	
Butyl ether	PNEC =	PNEC =	PNEC = 0.191mg/L	PNEC = 10mg/L	PNEC =
142-96-1 (>95)	0.0191mg/L	0.0734mg/kg		_	0.00391mg/kg soil
	_	sediment dw			dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Butyl ether 142-96-1 ( >95 )	PNEC = 0.00191mg/L	PNEC = 0.00734mg/kg			
	_	sediment dw			

## 8.2. Exposure controls

#### **Engineering Measures**

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

**Eye Protection** Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R)	See manufacturers	-	EN 374	(minimum requirement)
	recommendations			

**Skin and body protection** Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Di-n-butyl ether Revision Date 25-Jan-2024

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to

EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

141

When RPE is used a face piece Fit Test should be conducted

**Environmental exposure controls** Prevent product from entering drains.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

## 9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance Colorless Odor sweet

Odor ThresholdNo data availableMelting Point/Range-95 °C / -139 °FSoftening PointNo data availableBoiling Point/Range141 °C / 285.8 °F

Flammability (liquid) Flammable On basis of test data

Flammability (solid,gas) Not applicable Liquid

Explosion Limits Lower 0.9 Vol% Upper 8.5 Vol%

Opper 6.5 V01%

Flash Point 25 °C / 77 °F Method - No information available

Autoignition Temperature 175 - °C / 347 - °F Decomposition Temperature No data available

**pH** 5.2

Viscosity 0.69 mPa s at 20 °C

Water Solubility 0.03% (20°C)

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Componentlog PowButyl ether3.35

Vapor Pressure 6.4 mbar @ 20 °C

**Density / Specific Gravity** 0.768

Bulk DensityNot applicableLiquidVapor Density4.48(Air = 1.0)

Particle characteristics Not applicable (liquid)

## 9.2. Other information

Molecular Formula C8 H18 O Molecular Weight 130.23

**Explosive Properties** explosive air/vapour mixtures possible

# **SECTION 10: STABILITY AND REACTIVITY**

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

May form explosive peroxides on prolonged storage. Light sensitive. Air sensitive.

## 10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.

Di-n-butyl ether Revision Date 25-Jan-2024

**Hazardous Reactions** None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition. Exposure to air. Exposure to light.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids.

#### 10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO2).

## **SECTION 11: TOXICOLOGICAL INFORMATION**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Product Information**

(a) acute toxicity;

OralBased on available data, the classification criteria are not metDermalBased on available data, the classification criteria are not metInhalationBased on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Butyl ether	LD50 = 7400 mg/kg (Rat)	LD50 = 7741 mg/kg (Rabbit)	-

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

**Respiratory**Skin
No data available
No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; No data available

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system.

(i) STOT-repeated exposure; No data available

Target Organs No information available.

(j) aspiration hazard; No data available

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. delayed

Di-n-butyl ether Revision Date 25-Jan-2024

#### 11.2. Information on other hazards

**Endocrine Disrupting Properties** 

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## **SECTION 12: ECOLOGICAL INFORMATION**

12.1. Toxicity **Ecotoxicity effects** 

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Do not empty into drains. Contains a substance which is:. Harmful to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Butyl ether	LC50: 30.1 - 34.7 mg/L, 96h		
	flow-through (Pimephales		
	promelas)		
	prometas)		

Component	Microtox	M-Factor
Butyl ether	EC50 = 63.0 mg/L 5 min	

12.2. Persistence and degradability Not readily biodegradable

**Persistence** 

Insoluble in water, Persistence is unlikely, based on information available.

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

May have some potential to bioaccumulate

Component	log Pow	Bioconcentration factor (BCF)
Butyl ether	3.35	47 - 83 dimensionless

12.4. Mobility in soil

Spillage unlikely to penetrate soil The product is insoluble and floats on water The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces Will likely be mobile in the environment due to its volatility. Is not likely mobile in the environment due its low water solubility.

12.5. Results of PBT and vPvB assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

12.6. Endocrine disrupting

properties

**Endocrine Disruptor Information** 

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

**Persistent Organic Pollutant Ozone Depletion Potential** 

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

# **SECTION 13: DISPOSAL CONSIDERATIONS**

#### 13.1. Waste treatment methods

Waste from Residues/Unused **Products** 

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

**Contaminated Packaging** Dispose of this container to hazardous or special waste collection point. Empty containers

Di-n-butyl ether Revision Date 25-Jan-2024

retain product residue. (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

According to the European Waste Catalog, Waste Codes are not product specific, but **European Waste Catalogue (EWC)** 

application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the

application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not

empty into drains.

# **SECTION 14: TRANSPORT INFORMATION**

#### IMDG/IMO

UN1149 14.1. UN number

DIBUTYL ETHERS 14.2. UN proper shipping name

14.3. Transport hazard class(es) 3 14.4. Packing group Ш

#### **ADR**

14.1. UN number UN1149

DIBUTYL ETHERS 14.2. UN proper shipping name

14.3. Transport hazard class(es) 3 14.4. Packing group Ш

## IATA

UN1149 14.1. UN number

14.2. UN proper shipping name **DIBUTYL ETHERS** 

14.3. Transport hazard class(es) 14.4. Packing group Ш

No hazards identified 14.5. Environmental hazards

No special precautions required. 14.6. Special precautions for user

14.7. Maritime transport in bulk Not applicable, packaged goods according to IMO instruments

142-96-1

# **SECTION 15: REGULATORY INFORMATION**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **International Inventories**

Butyl ether

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Butyl ether	142-96-1	205-575-3	-	-	X	X	KE-27683	X	Х
Component	CAS No	TSCA	notific	nventory ation - Inactive	DSL	NDSL	AICS	NZIoC	PICCS

ACTIVE

Di-n-butyl ether Revision Date 25-Jan-2024

Legend: X - Listed '-' - Not Listed

**KECL** - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

## Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) -	REACH (1907/2006) -	REACH Regulation (EC
		Annex XIV - Substances	Annex XVII - Restrictions	1907/2006) article 59 -
		Subject to Authorization	on Certain Dangerous	Candidate List of
			Substances	Substances of Very High
				Concern (SVHC)
Butyl ether	142-96-1	-	Use restricted. See item	-
			75.	
			(see link for restriction	
			details)	

#### **REACH links**

https://echa.europa.eu/substances-restricted-under-reach

## Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Seveso III Directive (2012/18/E	
		Qualifying Quantities for Major Accident	Qualifying Quantities for Safety Report
		Notification	Requirements
Butyl ether	142-96-1	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

#### **National Regulations**

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Butyl ether	WGK1	

#### 15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

# **SECTION 16: OTHER INFORMATION**

## Full text of H-Statements referred to under sections 2 and 3

H226 - Flammable liquid and vapor

H315 - Causes skin irritation

H319 - Causes serious eye irritation

Di-n-butyl ether Revision Date 25-Jan-2024

H335 - May cause respiratory irritation

H412 - Harmful to aquatic life with long lasting effects

#### Legend

**CAS** - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b)

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances Substances List

**ENCS** - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from

Ships

ATE - Acute Toxicity Estimate **BCF** - Bioconcentration factor VOC - (Volatile Organic Compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

#### **Training Advice**

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Prepared Bv Health, Safety and Environmental Department

**Creation Date** 03-Dec-2010 **Revision Date** 25-Jan-2024

**Revision Summary** New emergency telephone response service provider.

# This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended. .

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**