

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Ethanol, denatured, 91.6%, 3.7% methanol, 1.9% MIBK, 1% heptane, 1% ethyl acetate, 1% toluene
Cat No. : 45844

Unique Formula Identifier (UFI) SRMJ-U6H2-TX0J-1QDR

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company
Avocado Research Chemicals Ltd.
(Part of Thermo Fisher Scientific)
Shore Road, Heysham
Lancashire, LA3 2XY,
United Kingdom
Office Tel: +44 (0) 1524 850506
Office Fax: +44 (0) 1524 850608

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

Poison Centre - Emergency information services
Ireland : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

Flammable liquids

Category 2 (H225)

SAFETY DATA SHEET

Ethanol, denatured, 91.6%, 3.7% methanol, 1.9% MIBK, 1% heptane, 1% ethyl acetate, 1% toluene

Revision Date 17-Mar-2024

Health hazards

Aspiration Toxicity
Serious Eye Damage/Eye Irritation
Carcinogenicity
Specific target organ toxicity - (single exposure)

Category 1 (H304)
Category 2 (H319)
Category 2 (H351)
Category 2 (H371)

Environmental hazards

Chronic aquatic toxicity

Category 3 (H412)

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H319 - Causes serious eye irritation
H351 - Suspected of causing cancer
H371 - May cause damage to organs
H412 - Harmful to aquatic life with long lasting effects
EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor/physician

2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
-----------	--------	-------	----------	---

SAFETY DATA SHEET

Ethanol, denatured, 91.6%, 3.7% methanol, 1.9% MIBK, 1% heptane, 1% ethyl acetate, 1% toluene

Revision Date 17-Mar-2024

Ethyl alcohol	64-17-5	200-578-6	91.6	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319)
Methyl alcohol	67-56-1	200-659-6	3.70	Flam. Liq. 2 (H225) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370)
Methylisobutyl ketone	108-10-1	EEC No. 203-550-1	1.70	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319) Acute Tox. 4 (H332) STOT SE 3 (H336) Carc. 2 (H351) [EUH066]
n-Heptane	142-82-5	EEC No. 205-563-8	1.00	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)
Toluene	108-88-3	203-625-9	1	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Repr. 2 (H361d) STOT RE 2 (H373)
Ethyl acetate	141-78-6	EEC No. 205-500-4	1	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319) STOT SE 3 (H336) EUH066

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Ethyl alcohol	Eye Irrit. 2 :: C>=50%	-	-
Methyl alcohol	STOT Single Exp. 1 :: >= 10 STOT Single Exp. 2 :: 3 - < 10	-	-
n-Heptane	-	1	-

Component	ECHA (RAC) ATE (Oral)	ECHA (RAC) ATE (Dermal)	ECHA (RAC) ATE (Inhalation)
Methylisobutyl ketone	-	-	ATE = 11 mg/L (vapour)

ECHA (RAC) - Committee for Risk Assessment - European Chemicals Agency

ATE - Acute Toxicity Estimate

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).

SAFETY DATA SHEET

Ethanol, denatured, 91.6%, 3.7% methanol, 1.9% MIBK, 1% heptane, 1% ethyl acetate, 1% toluene

Revision Date 17-Mar-2024

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Carbon dioxide (CO₂). Powder. Water spray. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂).

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

SAFETY DATA SHEET

Ethanol, denatured, 91.6%, 3.7% methanol, 1.9% MIBK, 1% heptane, 1% ethyl acetate, 1% toluene

Revision Date 17-Mar-2024

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Store under an inert atmosphere. Keep container tightly closed in a dry and well-ventilated place. Protect from moisture. Keep away from heat, sparks and flame.

Technical Rules for Hazardous Substances (TRGS) 510 Class 3
Storage Class (LGK) (Germany)

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Ethyl alcohol	TWA: 1000 ppm TWA; 1920 mg/m ³ TWA WEL - STEL: 3000 ppm STEL; 5760 mg/m ³ STEL		STEL: 1000 ppm 15 min
Methyl alcohol	WEL - TWA: 200 ppm TWA; 266 mg/m ³ TWA WEL - STEL: 250 ppm STEL; 333 mg/m ³ STEL	TWA: 200 ppm 8 hr TWA: 260 mg/m ³ 8 hr Skin	TWA: 200 ppm 8 hr. TWA: 260 mg/m ³ 8 hr. STEL: 600 ppm 15 min STEL: 780 mg/m ³ 15 min Skin
Methylisobutyl ketone	STEL: 100 ppm 15 min STEL: 416 mg/m ³ 15 min TWA: 50 ppm 8 hr TWA: 208 mg/m ³ 8 hr Skin	TWA: 20 ppm (8h) TWA: 83 mg/m ³ (8h) STEL: 50 ppm (15min) STEL: 208 mg/m ³ (15min)	TWA: 20 ppm 8 hr. TWA: 83 mg/m ³ 8 hr. STEL: 50 ppm 15 min STEL: 208 mg/m ³ 15 min Skin
n-Heptane	STEL: 1500 ppm 15 min STEL: 6255 mg/m ³ 15 min TWA: 500 ppm 8 hr TWA: 2085 mg/m ³ 8 hr	TWA: 500 ppm (8h) TWA: 2085 mg/m ³ (8h)	TWA: 500 ppm 8 hr. TWA: 2085 mg/m ³ 8 hr. STEL: 1500 ppm 15 min STEL: 6255 mg/m ³ 15 min
Toluene	STEL: 100 ppm 15 min STEL: 384 mg/m ³ 15 min TWA: 50 ppm 8 hr TWA: 191 mg/m ³ 8 hr Skin	TWA: 50 ppm (8hr) TWA: 192 mg/m ³ (8hr) STEL: 100 ppm (15min) STEL: 384 mg/m ³ (15min) Skin	TWA: 192 mg/m ³ 8 hr. TWA: 50 ppm 8 hr. STEL: 384 mg/m ³ 15 min STEL: 100 ppm 15 min Skin
Ethyl acetate	STEL: 1468 mg/m ³ 15 min STEL: 400 ppm 15 min TWA: 734 mg/m ³ 8 hr TWA: 200 ppm 8 hr	TWA: 734 mg/m ³ (8h) TWA: 200 ppm (8h) STEL: 1468 mg/m ³ (15min) STEL: 400 ppm (15min)	TWA: 734 mg/m ³ 8 hr. TWA: 200 ppm 8 hr. STEL: 1468 mg/m ³ 15 min STEL: 400 ppm 15 min

Biological limit values

SAFETY DATA SHEET

Ethanol, denatured, 91.6%, 3.7% methanol, 1.9% MIBK, 1% heptane, 1% ethyl acetate, 1% toluene

Revision Date 17-Mar-2024

List source(s): **UK** - Biological Monitoring Guidance Values provided by the UK's Health and Safety Executive (HSE) Control of Substances Hazardous to Health Regulations (COSHH) 2002 (as amended) and EH40/2005.

Component	United Kingdom	European Union
Methylisobutyl ketone	4-Methylpentan-2-one: 20 µmol/L urine post shift	

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Oral)	Acute effects systemic (Oral)	Chronic effects local (Oral)	Chronic effects systemic (Oral)
Ethyl alcohol 64-17-5 (91.6)		DNEL = 87 mg/kg bw/d		

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Ethyl alcohol 64-17-5 (91.6)				DNEL = 343mg/kg bw/day
Methyl alcohol 67-56-1 (3.70)		DNEL = 20mg/kg bw/day		DNEL = 20mg/kg bw/day
Methylisobutyl ketone 108-10-1 (1.70)				DNEL = 11.8mg/kg bw/day
n-Heptane 142-82-5 (1.00)				DNEL = 300mg/kg bw/day
Toluene 108-88-3 (1)				DNEL = 384mg/kg bw/day
Ethyl acetate 141-78-6 (1)				DNEL = 63mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Ethyl alcohol 64-17-5 (91.6)	DNEL = 1900mg/m ³			DNEL = 950mg/m ³
Methyl alcohol 67-56-1 (3.70)	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³
Methylisobutyl ketone 108-10-1 (1.70)	DNEL = 208mg/m ³	DNEL = 208mg/m ³	DNEL = 83mg/m ³	DNEL = 83mg/m ³
n-Heptane 142-82-5 (1.00)				DNEL = 2085mg/m ³
Toluene 108-88-3 (1)	DNEL = 384mg/m ³	DNEL = 384mg/m ³	DNEL = 192mg/m ³	DNEL = 192mg/m ³
Ethyl acetate 141-78-6 (1)	DNEL = 1468 mg/m ³ 400 ppm	DNEL = 1468 mg/m ³ 400 ppm	DNEL = 734 mg/m ³ 200 ppm	DNEL = 734mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Methyl alcohol 67-56-1 (3.70)	PNEC = 20.8mg/L	PNEC = 77mg/kg sediment dw	PNEC = 1540mg/L	PNEC = 100mg/L	PNEC = 100mg/kg soil dw
Methylisobutyl ketone 108-10-1 (1.70)	PNEC = 0.6mg/L	PNEC = 8.27mg/kg sediment dw	PNEC = 1.5mg/L	PNEC = 27.5mg/L	PNEC = 1.3mg/kg soil dw
Toluene 108-88-3 (1)	PNEC = 0.68mg/L	PNEC = 16.39mg/kg sediment dw	PNEC = 0.68mg/L	PNEC = 13.61mg/L	PNEC = 2.89mg/kg soil dw
Ethyl acetate 141-78-6 (1)	PNEC = 0.24mg/L	PNEC = 1.15mg/kg sediment dw	PNEC = 1.65mg/L	PNEC = 650mg/L	PNEC = 0.148mg/kg soil dw

Component	Marine water	Marine water	Marine water	Food chain	Air
-----------	--------------	--------------	--------------	------------	-----

SAFETY DATA SHEET

Ethanol, denatured, 91.6%, 3.7% methanol, 1.9% MIBK, 1% heptane, 1% ethyl acetate, 1% toluene

Revision Date 17-Mar-2024

		sediment	intermittent		
Methyl alcohol 67-56-1 (3.70)	PNEC = 2.08mg/L	PNEC = 7.7mg/kg sediment dw			
Methylisobutyl ketone 108-10-1 (1.70)	PNEC = 0.06mg/L	PNEC = 0.83mg/kg sediment dw			
Toluene 108-88-3 (1)	PNEC = 0.68mg/L	PNEC = 16.39mg/kg sediment dw			
Ethyl acetate 141-78-6 (1)	PNEC = 0.024mg/L	PNEC = 0.115mg/kg sediment dw		PNEC = 0.2g/kg food	

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Neoprene	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection

Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

In case of insufficient ventilation, wear suitable respiratory equipment

Recommended Filter type: SCBA

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State

Liquid

Appearance

Colorless

Odor

No information available

SAFETY DATA SHEET

Ethanol, denatured, 91.6%, 3.7% methanol, 1.9% MIBK, 1% heptane, 1% ethyl acetate, 1% toluene

Revision Date 17-Mar-2024

Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	78 °C / 172.4 °F	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	8 °C / 46.4 °F	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	No data available	
Water Solubility	Miscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Ethyl alcohol	-0.32	
Methyl alcohol	-0.74	
Methylisobutyl ketone	1.9	
n-Heptane	4.66	
Toluene	2.73	
Ethyl acetate	0.73	
Vapor Pressure	23 hPa @ 20 °C	
Density / Specific Gravity	0.789 g/cm3	@ 20 °C
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Explosive Properties Vapors may form explosive mixtures with air

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity None known, based on information available

10.2. Chemical stability Hygroscopic.

10.3. Possibility of hazardous reactions

Hazardous Polymerization No information available.
Hazardous Reactions None under normal processing.

10.4. Conditions to avoid Exposure to moist air or water. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials Oxidizing agent.

10.6. Hazardous decomposition products Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

SAFETY DATA SHEET

Ethanol, denatured, 91.6%, 3.7% methanol, 1.9% MIBK, 1% heptane, 1% ethyl acetate, 1% toluene

Revision Date 17-Mar-2024

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl alcohol	LD50 = 10470 mg/kg OECD 401 (Rat) 3450 mg/kg (Mouse)	-	LC50 = 117-125 mg/l (4h) OECD 403 (rat) 20000 ppm/10H (rat)
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h
Methylisobutyl ketone	LD50 = 2080 mg/kg (Rat)	LD50 = 3000 mg/kg (Rabbit)	LC50 2000 - 4000 ppm (Rat) 4 h
n-Heptane	>2000 mg/kg (rat)	LD50 = 3000 mg/kg (Rabbit)	LC50 > 73.5 mg/L (Rat) 4 h
Toluene	> 5000 mg/kg (Rat)	LD50 = 12000 mg/kg (Rabbit)	26700 ppm (Rat) 1 h
Ethyl acetate	10,200 mg/kg (Rat)	> 20 mL/kg (Rabbit) > 18000 mg/kg (Rabbit)	58 mg/l (rat; 8 h)

Component	ECHA (RAC) ATE (Oral)	ECHA (RAC) ATE (Dermal)	ECHA (RAC) ATE (Inhalation)
Methylisobutyl ketone	-	-	ATE = 11 mg/L (vapour)

ECHA (RAC) - Committee for Risk Assessment - European CHemicals Agency

ATE - Acute Toxicity Estimate

(b) skin corrosion/irritation;

No data available

(c) serious eye damage/irritation;

Category 2

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

Component	Test method	Test species	Study result
Ethyl alcohol 64-17-5 (91.6)	Mouse Ear Swelling Test (MEST)	mouse	non-sensitising
	----- OECD Test Guideline 429 Local Lymph Node Assay	mouse	non-sensitising
Methyl alcohol 67-56-1 (3.70)	OECD Test Guideline 406 Guinea Pig Maximisation Test (GPMT)	guinea pig	non-sensitising
Ethyl acetate 141-78-6 (1)	OECD Test Guideline 406	guinea pig	- non-sensitising

(e) germ cell mutagenicity;

No data available

Component	Test method	Test species	Study result
Ethyl alcohol 64-17-5 (91.6)	AMES test OECD Test Guideline 471	in vitro Bacteria	negative
	----- Gene cell mutation OECD Test Guideline 476	in vitro Mammalian	negative
Ethyl acetate 141-78-6 (1)	OECD Test Guideline 471 AMES test	in vitro Bacteria	negative
	----- OECD Test Guideline 473 Chromosomal aberration assay	in vitro Mammalian	negative

SAFETY DATA SHEET

Ethanol, denatured, 91.6%, 3.7% methanol, 1.9% MIBK, 1% heptane, 1% ethyl acetate, 1% toluene

Revision Date 17-Mar-2024

	OECD Test Guideline 476 Gene cell mutation	in vitro Mammalian	negative
	OECD Test Guideline 474 Mouse micronucleus assay	in vivo Mammalian	negative

(f) carcinogenicity;

Category 2

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Methylisobutyl ketone				Group 2B

(g) reproductive toxicity;

No data available

Component	Test method	Test species / Duration	Study result
Ethyl alcohol 64-17-5 (91.6)	OECD Test Guideline 416 ----- OECD Test Guideline 414	Oral / mouse 2 Generation ----- Inhalation / Rat	NOAEL = 13.8 g/kg/day ----- NOAEC = 16000 ppm
Methyl alcohol 67-56-1 (3.70)	OECD Test Guideline 416	Rat / Inhalation 2 Generation	NOAEC = 1.3 mg/l (air)
Methylisobutyl ketone 108-10-1 (1.70)	OECD Test Guideline 414	Rat Inhalation	NOAEL = 4.1 mg/l
Ethyl acetate 141-78-6 (1)	OECD Test Guideline 416 ----- OECD Test Guideline 414	Oral mouse 2 Generation ----- Inhalation Rat	NOAEL = 26400 mg/kg bw/day ----- NOAEC = 73300 mg/m ³

(h) STOT-single exposure;

Category 2

Results / Target organs

Respiratory system, Central nervous system (CNS), Optic nerve.

(i) STOT-repeated exposure;

No data available

Target Organs

None known.

(j) aspiration hazard;

Category 1

Symptoms / effects, both acute and delayed

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

The product contains following substances which are hazardous for the environment. Contains a substance which is: Toxic to aquatic organisms.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Ethyl alcohol	Fathead minnow (Pimephales promelas) LC50 = 14200	EC50 = 9268 mg/L/48h EC50 = 10800 mg/L/24h	EC50 (72h) = 275 mg/l (Chlorella vulgaris)

SAFETY DATA SHEET

Ethanol, denatured, 91.6%, 3.7% methanol, 1.9% MIBK, 1% heptane, 1% ethyl acetate, 1% toluene

Revision Date 17-Mar-2024

	mg/l/96h		
Methyl alcohol	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 > 10000 mg/L 24h	
Methylisobutyl ketone	LC50: 496 - 514 mg/L, 96h flow-through (Pimephales promelas)	EC50: 4280.0 mg/L/24h EC50: 170 mg/L/48h EC50: 4280.0 mg/L/24h	EC50: 400 mg/L/96h
n-Heptane	LC50: = 375.0 mg/L, 96h (Cichlid fish)	EC50: >10 mg/L/24h	
Toluene	50-70 mg/L LC50 96 h 5-7 mg/L LC50 96 h 15-19 mg/L LC50 96 h 28 mg/L LC50 96 h 12 mg/L LC50 96 h	EC50: = 11.5 mg/L, 48h (Daphnia magna) EC50: 5.46 - 9.83 mg/L, 48h Static (Daphnia magna)	EC50: = 12.5 mg/L, 72h static (Pseudokirchneriella subcapitata) EC50: > 433 mg/L, 96h (Pseudokirchneriella subcapitata)
Ethyl acetate	Fathead minnow: LC50: 230 mg/l/ 96h Gold orfe: LC50: 270 mg/L/48h	EC50 = 717 mg/L/48h	EC50 = 3300 mg/L/48h

Component	Microtox	M-Factor
Ethyl alcohol	Photobacterium phosphoreum:EC50 = 34634 mg/L/30 min Photobacterium phosphoreum:EC50 = 35470 mg/L/5 min	
Methyl alcohol	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	
Methylisobutyl ketone	EC50 = 79.6 mg/L 5 min	
n-Heptane		1
Toluene	EC50 = 19.7 mg/L 30 min	
Ethyl acetate	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h	

12.2. Persistence and degradability

Persistence

Persistence is unlikely, based on information available.

Component	Degradability
Ethyl alcohol 64-17-5 (91.6)	OECD 301E = 94%
Methyl alcohol 67-56-1 (3.70)	DT50 ~ 17.2d >94% after 20d
Methylisobutyl ketone 108-10-1 (1.70)	83 % (28 d) (OECD 301F)
Toluene 108-88-3 (1)	86% (20d)
Ethyl acetate 141-78-6 (1)	79 % (20 d) (OECD 301 D)

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Ethyl alcohol	-0.32	No data available
Methyl alcohol	-0.74	<10 dimensionless
Methylisobutyl ketone	1.9	No data available
n-Heptane	4.66	No data available
Toluene	2.73	90
Ethyl acetate	0.73	30 dimensionless

12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces Will likely be mobile in the environment due to its volatility. Disperses rapidly in air

SAFETY DATA SHEET

Ethanol, denatured, 91.6%, 3.7% methanol, 1.9% MIBK, 1% heptane, 1% ethyl acetate, 1% toluene

Revision Date 17-Mar-2024

12.5. Results of PBT and vPvB assessment

No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance

This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number

UN1170

14.2. UN proper shipping name

Ethanol solution

14.3. Transport hazard class(es)

3

14.4. Packing group

II

ADR

14.1. UN number

UN1170

14.2. UN proper shipping name

Ethanol solution

14.3. Transport hazard class(es)

3

14.4. Packing group

II

IATA

14.1. UN number

UN1170

14.2. UN proper shipping name

Ethanol solution

14.3. Transport hazard class(es)

3

14.4. Packing group

II

14.5. Environmental hazards

No hazards identified

SAFETY DATA SHEET

Ethanol, denatured, 91.6%, 3.7% methanol, 1.9% MIBK, 1% heptane, 1% ethyl acetate, 1% toluene

Revision Date 17-Mar-2024

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

China, X = listed, Australia, U.S.A. (TSCA), Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Australia (AICS), Korea (KECL), China (IECSC), Japan (ENCS), Philippines (PICCS), Taiwan (TCSI), Japan (ISHL), New Zealand (NZIoC), Japan (ISHL). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Ethyl alcohol	64-17-5	200-578-6	-	-	X	X	KE-13217	X	X
Methyl alcohol	67-56-1	200-659-6	-	-	X	X	KE-23193	X	X
Methylisobutyl ketone	108-10-1	203-550-1	-	-	X	X	KE-24725	X	X
n-Heptane	142-82-5	205-563-8	-	-	X	X	KE-18271	X	X
Toluene	108-88-3	203-625-9	-	-	X	X	KE-33936	X	X
Ethyl acetate	141-78-6	205-500-4	-	-	X	X	KE-00047	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Ethyl alcohol	64-17-5	X	ACTIVE	X	-	X	X	X
Methyl alcohol	67-56-1	X	ACTIVE	X	-	X	X	X
Methylisobutyl ketone	108-10-1	X	ACTIVE	X	-	X	X	X
n-Heptane	142-82-5	X	ACTIVE	X	-	X	X	X
Toluene	108-88-3	X	ACTIVE	X	-	X	X	X
Ethyl acetate	141-78-6	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Ethyl alcohol	64-17-5	-	-	-
Methyl alcohol	67-56-1	-	Use restricted. See item 69. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Methylisobutyl ketone	108-10-1	-	Use restricted. See item 75. (see link for restriction details)	-
n-Heptane	142-82-5	-	Use restricted. See item 75. (see link for restriction details)	-
Toluene	108-88-3	-	Use restricted. See item 48. (see link for restriction details) Use restricted. See item 75.	-

SAFETY DATA SHEET

Ethanol, denatured, 91.6%, 3.7% methanol, 1.9% MIBK, 1% heptane, 1% ethyl acetate, 1% toluene

Revision Date 17-Mar-2024

			(see link for restriction details)	
Ethyl acetate	141-78-6	-	Use restricted. See item 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Ethyl alcohol	64-17-5	Not applicable	Not applicable
Methyl alcohol	67-56-1	500 tonne	5000 tonne
Methylisobutyl ketone	108-10-1	Not applicable	Not applicable
n-Heptane	142-82-5	Not applicable	Not applicable
Toluene	108-88-3	Not applicable	Not applicable
Ethyl acetate	141-78-6	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Ethyl alcohol	WGK1	
Methyl alcohol	WGK 2	Class I : 20 mg/m³ (Massenkonzentration)
Methylisobutyl ketone	WGK1	
n-Heptane	WGK2	
Toluene	WGK3	
Ethyl acetate	WGK1	

Component	France - INRS (Tables of occupational diseases)
Ethyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84
Methyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84
Methylisobutyl ketone	Tableaux des maladies professionnelles (TMP) - RG 84
n-Heptane	Tableaux des maladies professionnelles (TMP) - RG 84
Toluene	Tableaux des maladies professionnelles (TMP) - RG 4bis, RG 84
Ethyl acetate	Tableaux des maladies professionnelles (TMP) - RG 84

Component	Switzerland - Ordinance on the	Switzerland - Ordinance on	Switzerland - Ordinance of the
-----------	--------------------------------	----------------------------	--------------------------------

SAFETY DATA SHEET

Ethanol, denatured, 91.6%, 3.7% methanol, 1.9% MIBK, 1% heptane, 1% ethyl acetate, 1% toluene

Revision Date 17-Mar-2024

	Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Incentive Taxes on Volatile Organic Compounds (OVOC)	Rotterdam Convention on the Prior Informed Consent Procedure
Ethyl alcohol 64-17-5 (91.6)		Group I	
Methyl alcohol 67-56-1 (3.70)	Prohibited and Restricted Substances	Group I	
Methylisobutyl ketone 108-10-1 (1.70)		Group I	
n-Heptane 142-82-5 (1.00)	Prohibited and Restricted Substances	Group I	
Toluene 108-88-3 (1)	Prohibited and Restricted Substances	Group I	
Ethyl acetate 141-78-6 (1)		Group I	

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor
H301 - Toxic if swallowed
H304 - May be fatal if swallowed and enters airways
H311 - Toxic in contact with skin
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H331 - Toxic if inhaled
H332 - Harmful if inhaled
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer
H361d - Suspected of damaging the unborn child
H370 - Causes damage to organs
H371 - May cause damage to organs
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects
H412 - Harmful to aquatic life with long lasting effects
EUH066 - Repeated exposure may cause skin dryness or cracking

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

SAFETY DATA SHEET

Ethanol, denatured, 91.6%, 3.7% methanol, 1.9% MIBK, 1% heptane, 1% ethyl acetate,
1% toluene

Revision Date 17-Mar-2024

BCF - Bioconcentration factor

VOC - (Volatile Organic Compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Prepared By

Health, Safety and Environmental Department

Revision Date

17-Mar-2024

Revision Summary

New emergency telephone response service provider.

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet